



DOVE
ASSOCIATES

Horticultural Consultants

Weggs Farm

Common Road

Dickleburgh, DISS

Norfolk IP21 4PJ

Tel: 01379 741200

Fax: 01379 741800

Email: info@dovebugs.co.uk

www.dovebugs.co.uk

Information Conductivity

Conductivity meters

Conductivity meters are an excellent and useful piece of equipment for measuring the level of nutrients in liquid feeds and compost. If you take weekly readings of compost you can soon build up a picture of CRF nutrient release and optimum growth, so you can use liquid feeding as a top up.

The conductivity meters we supply measure in micro Seimens x10 or milli Seimens mS. A reading of 25 on the pen is 250 micro Seimens or μ S.

Compost measurement.

Conductivity is changed by temperature so try to make measurements at a known water temperature. We suggest you use the following as a guide to simple nursery use, making sure you follow the same procedure each time to make your readings relative.

Take a compost sample from around 20 pots taking it from within the compost body ideally by corer. Remove any CRF granules to avoid high and non-representative readings. Add 2½ times nursery irrigation water to a compost sample. Stir well and allow to stand for around half an hour in the office to settle and bring up to room temperature, then dip the pen into the sample.

For readings to be of use you must first take a reading of plain water. This figure is taken away from the sample to arrive at low, optimum and high levels for you.

General nursery stock

Readings of:

- 150 μ S and lower are low
- 150 μ S to 400 μ S are optimum
- Above 400 μ S are high

Heathers and some alpinas e.g. as *Lithodora*

Treat 300 μ S as the optimum level.

To relate this to your nursery and assuming your plain water was 400 μ S, the pen would be showing levels of:

- 550 μ S and under for low (150+400)
- 550 μ S to 800 μ S for optimum (400+400)
- over 800 μ S for high

Use plant protection products safely. Always read the label and product information before use

Dove Associates shall in no event be liable for any loss or damage caused by the products mentioned in this document.

© Dove Associates 07/03/17

Liquid feed monitoring

For liquid feed checking take a sample of stock solution and dilute it with 100 equal volumes of water to produce a 1:100 standard solution, or with 200 volumes for 1:200 standard solution. These standards can be used as references for checking the efficiency of diluter and injector settings. Note that urea will not ionise the water and so cannot be used for this type of measurement. We have written a computer programme to run on Excel to calculate both the pH effect and conductivity of home made liquid feeds. Contact the office for details.

Pesticides

If you apply pesticides through a drip irrigation system the application rates can be checked by adding small amounts of liquid feed to the mixture and measuring the conductivity of the solution flowing from the nozzle. Remember the solution is a pesticide and the personal protective clothing stated on the pesticide label must be used when checking.

The pen meter model is available at £127.50. It takes four coin cells which are priced at £1.73 each. Calibration sachets (1413 μ S) are £1.25 each and 460ml bottles of calibration solution (also 1413 μ S) are £23.75 each. All prices exclude VAT at the standard rate and postage.

- Waterproof (they even float!)
- Dual-level LCD displaying EC or TDS and temperature
- Self-check at start up, displaying remaining battery life and ensuring proper working condition
- Stability indicator and hold feature
- Stainless steel temperature probe for faster and more precise temperature measurement
- Automatic calibration and temperature compensation
- User adjustable EC/TDS conversion factor and temperature coefficient factors
- EC/TDS graphite electrode for greater accuracy and reduced contamination
- Auto shut-off
- °C/°F



technical specification		Dist 5 (HI 98311)	Dist 6 (HI 98312)
Range	EC	0 to 3999 μ S/cm	0.0 to 20.00 mS/cm
	TDS	0 to 2000 ppm	0.00 to 10.00 ppt
	Temperature		0.0 to 60.0°C
Resolution	EC	1 μ S/cm	0.01 mS/cm
	TDS	1 ppm	0.01 ppt
	Temperature		0.1°C
Accuracy (@ 20°C)	EC		+/-2% Full Scale
	TDS		+/-2% Full Scale
	Temperature		+/-0.5°C
EC/TDS Calibration		Automatic	Automatic
		1 point at 1413 μ S/cm	1 point at 1288 mS/cm
EC/TDS Conversion Factor		Adjustable from 0.45 to 1.00	
Temperature Compensation		BETA (β) = adjustable from 0.0 to 2.4 per °C in increments of 0.1	
Battery Type/Life		4 x 1.5V / 100 hours	
Auto-shut-off		After 8 minutes	
Dimensions		163 x 40 x 26mm	
Weight		85g	

Use plant protection products safely. Always read the label and product information before use

Dove Associates shall in no event be liable for any loss or damage caused by the products mentioned in this document.

© Dove Associates 07/03/17